

Calibration Kits for Signet 4150 Turbidimeter



Calibration Kit, 100,
10 & 0.02 NTU/FNU



Calibration Kit, 1000,
10 & 0.02 NTU/FNU

The Calibration Standard kits contain fluids in special cuvette bottles that are used to compare the clarity of the process water against the standard to calibrate the turbidity instrument. The standard kits come in two pre-mixed, calibrated ranges.

The 0-100 version is generally used for measuring the turbidity of clean, potable water applications. The 0-1,000 version is used to measure water that has a turbidity which may exceed 100, such as water in a reclamation plant.


Features

- Stable pre-mixed standards that are certified accurate
- Sealed calibration cuvettes
- Shelf life - 18 months
- Easy to follow instructions
- Kits for easy use

Applications

- Potable Water Filtration
- Water Reclamation
- Food and Beverage Plants

System Overview



Ordering Information

Mfr. Part No.	Code	Description
3822-4001	159 001 585	*Calibration Kit, Turbidity, 100, 10 & 0.02 NTU/FNU
3822-4003	159 001 586	*Calibration Kit, Turbidity, 1000, 10 & 0.02 NTU/FNU
4150-0007	159 001 602	Replacement cuvette set (3 glass cuvettes)
4150-0004	159 001 589	Replacement cuvette with ultrasonic transducer

* Material Safety Data Sheets (MSDS) are available online at www.gfsignet.com



Tel: +44 (0) 1706 869777

E-mail: sales@desal.co.uk

Web: www.desal.co.uk

3-4150-3822.099 Rev B (11/11)

© Georg Fischer Signet LLC

3401 Aerojet Avenue, El Monte, CA 91731-2882 U.S.A. • Tel. (626) 571-2770 • Fax (626) 573-2057 • www.gfsignet.com • e-mail: signet.ps@georgfischer.com
 Specifications subject to change without notice. All rights reserved. All corporate names and trademarks stated herein are the property of their respective companies.