



Tel: +44 (0) 1706 869777
 E-mail: sales@desal.co.uk
 Web: www.desal.co.uk

AMBERLITE™ IR120 H

Industrial Grade Strong Acid Cation Exchanger

Introduction

AMBERLITE IR120 H resin is a gel type strongly acidic cation exchange resin of the sulfonated polystyrene type. It is used for water demineralisation (in H⁺ form) in co-flow regenerated units.

AMBERLITE IR120 H resin is an excellent general purpose cation exchange resin that can be used for a wide variety of water demineralisation applications.

Properties

Physical form	Amber spherical beads
Matrix	Styrene divinylbenzene copolymer
Functional group	Sulfonic acid
Ionic form as shipped	H ⁺
Total exchange capacity	≥ 1.80 eq/L (H ⁺ form)
Moisture holding capacity	53 to 58 % (H ⁺ form)
Shipping weight	800 g/L
Particle size	
Uniformity coefficient	≤ 1.8
Harmonic mean size	0.620 to 0.830 mm < 0.300 mm 2 % max
Maximum reversible swelling	Na ⁺ → H ⁺ ≤ 11 %

Suggested Operating Conditions

Maximum operating temperature	135 °C
Minimum bed depth	700 mm
Service flow rate	5 to 40 BV*/h
Regeneration	
Regenerants	HCl H ₂ SO ₄
Level (g/L)	50 to 150 60 to 240
Concentration (%)	5 to 8 0.7 to 6
Minimum contact time	30 minutes
Slow rinse	2 BV at regeneration flow rate
Fastrinse	2 to 4 BV at service flow rate

Hydraulic Characteristics

Figure 1 shows the bed expansion of AMBERLITE IR120 H resin as a function of backwash flow rate and water temperature.

Figure 2 shows the pressure drop data for AMBERLITE IR120 H resin, as a function of service flow rate and water temperature. Pressure drop data are valid at the start of the service run with clear water and a correctly classified bed.

Fig. 1: Bed Expansion





Fig. 2 : Pressure Drop



For more information about DOW™ resins, call the Dow Water & Process Solutions business:

North America: 1-800-447-4369
 Latin America: (+55) 11-5188-9222
 Europe: +800-3-694-6367
 Italy: +800-783-825
 South Africa: +0800 99 5078
 Pacific: +8007776 7776
 China: +400 889-0789

<http://www.dowwaterandprocess.com>

Notice: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

